

**FAG****61814-2RSR**

Deep groove ball bearing

Deep groove ball bearing 618..-2RSR, single row, seals, steel sheet metal cage

Technical information

**Your current product variant**

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	90 mm	Outside diameter
B	10 mm	Width
C _r	13.200 N	Basic dynamic load rating, radial
C _{0r}	12.400 N	Basic static load rating, radial
C _{ur}	820 N	Fatigue load limit, radial
n _G	3.500 1/min	Limiting speed
m	0,139 kg	Weight

Mounting dimensions

d _{a min}	73,2 mm	Minimum diameter shaft shoulder
D _{a max}	86,8 mm	Maximum diameter of housing shoulder
r _{a max}	0,6 mm	Maximum fillet radius



Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	83,57 mm	Shoulder diameter outer ring
D_2	85,5 mm	Caliber diameter outer ring
d_1	76,6 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	16,1	Calculation factor
-------	------	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides