

Cresto, Energy Single-Flex H 140Kg 1301-F

Fall arrest lanyard 1301-F

-

EN 355 : 2002



Product description

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Energy Single-Flex has the same functions as Energy Twin-Flex except that it has only one webbing and one hook instead of two. Energy Single-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.8 meters. At the beginning of the rope there is an external absorber mounted which is released in case of a fall and catches you. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

Product properties

Brand	Cresto
Attaching connector 1	Oval twist lock carabiner in aluminum, mounted with captive pin
Attaching connector 2	Big aluminum hook with 63 mm opening
Minimum breaking strength - MBS (kN)	15
Energy absorber	Yes
Fall indicator	Yes
Maximum load (kg)	140
Maximum number of users	1
Mechanics	Tear-webbing absorber
Maximum working temperature (c)	100
Minimum working temperature (c)	-40
PPE-category	Category 3
Declaration of Conformity	Yes

EN-standard	EN 355 : 2002
Warranty	2+1 year when registered in Inspector
Identification	Serial number
Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
RFID	Yes

Article information

Article number	Article name	Colors	H(cm)	Net weight (kg)
012203201	Cresto, Energy Single-Flex H 140Kg, 1.8m	Black	180	1.12

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
012203201	Cresto, Energy Single-Flex H 140Kg, 1.8m	7350015790711	56090000	46182302	Slovakia

Article number	Article name	Packaging type	W(cm)	H(cm)	L(cm)	Gross weight (kg)	Pieces / Pack
012203201	Cresto, Energy Single-Flex H 140Kg, 1.8m	Carton	0	0	0	1.14	1