

## P181050

### AIR FILTER, PRIMARY FINNED

#### Why Choose Donaldson Air Filters?

Strong, pliable gasket is compressed against the air cleaner housing to create a tight seal.

- High-efficiency cellulose media performs across a wide range of heavy-duty engine applications.
- Corrosion resistant, coated steel liners support media during operation and help maximize airflow.
- Pleatloc™ feature ensures uniform pleat spacing and prevents media from bunching to promote longer service life.



#### Attributes

Outer Diameter	104 mm (4.09 inch)
Inner Diameter	62.9 mm (2.48 inch)
Length	254 mm (10.00 inch)
Minor OD	16.76 mm (0.66 inch)
Efficiency	99.9
Efficiency Test Std	ISO 5011
Family	FWA
Type	Primary

Style	Finned
Media Type	Cellulose

---

#### Packaged Dimensions

Packaged Length	0.15 M
Packaged Width	0.15 M
Packaged Height	0.28M
Packaged Weight	0.5 KG
Packaged Volume	0.0063 M3

---

#### Other Information

Country of Origin	Czech Republic
HTS Code	84213100 90
UPC Code	742330025512

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.