

ISO 4017 A4-80
Sechskantschrauben mit Gewinde bis Kopf
ISO 4017 A4-80
Hexagon head screws

ISO 4017
A4-80
Alternative Norm
ehemals DIN 933

d	M 20	M 22	M 24
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
10			
12			
14			
16			
18			
20			
22			
25			
28			
30	401748020 30		
35	401748020 35		
40	401748020 40	401748022 40	401748024 40
45	401748020 45	401748022 45	401748024 45
50	401748020 50	401748022 50	401748024 50
55	401748020 55	401748022 55	401748024 55
60	401748020 60	401748022 60	401748024 60
65	401748020 65	401748022 65	401748024 65
70	401748020 70	401748022 70	401748024 70
75	401748020 75	401748022 75	401748024 75
80	401748020 80	401748022 80	401748024 80
85	401748020 85	401748022 85	401748024 85
90	401748020 90	401748022 90	401748024 90
95	401748020 95	401748022 95	401748024 95
100	401748020 100	401748022 100	401748024 100
110	401748020 110	401748022 110	401748024 110
120	401748020 120	401748022 120	401748024 120
130	401748020 130	401748022 130	401748024 130
140	401748020 140	401748022 140	401748024 140
150	401748020 150	401748022 150	401748024 150
160	401748020 160		401748024 160
170	401748020 170		401748024 170
180	401748020 180		401748024 180
190	401748020 190		401748024 190
200	401748020 200		401748024 200



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.

*quality inspection from M6
including to M24 available on
demand.*

	25 ≥ 180 20	25 ≥ 110 10	10 ≥ 180 5
k	12,5	14	15
Antrieb	SW 30	SW 34	SW 36