

**FAG****S61900-2Z>N**

## Deep groove ball bearing

Deep groove ball bearing S619..-2Z,  
corrosion-resistant materials, single row,  
shields, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	10 mm	Bore diameter
D	22 mm	Outside diameter
B	6 mm	Width
C <sub>r</sub>	2.850 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.270 N	Basic static load rating, radial
C <sub>ur</sub>	79 N	Fatigue load limit, radial
n <sub>G</sub>	41.000 1/min	Limiting speed
n <sub>gr</sub>	27.000 1/min	Reference speed
≈m	10 g	Weight



### Mounting dimensions

$d_{a \min}$	12 mm	Minimum diameter shaft shoulder
$D_{a \max}$	20 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	18,4 mm	Shoulder diameter outer ring
$D_2$	19,5 mm	Caliber diameter outer ring
$d_1$	13,6 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	14	Calculation factor
-------	----	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Protected against rust