

Rotary distributor GF-3/8

Part number: 2095

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|--|
| Nominal size | 15 mm |
| Mounting position | optional |
| Operating pressure complete temperature range | -0.095 MPa ... 1 MPa |
| Operating pressure complete temperature range | -0.95 bar ... 10 bar |
| Operating pressure complete temperature range | -13.775 psi ... 145 psi |
| Standard flow rate 1-2.1 (6->0) | 4641 l/min |
| Standard flow rate 1-2.X open (6->0) | 4647 l/min |
| Standard nominal flow rate 1.1-2.1 | 2969 l/min |
| Max. rotational speed | 300 rpm |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Media temperature | -10 °C ... 60 °C |
| Ambient temperature | -10 °C ... 60 °C |
| Product weight | 270 g |
| Pneumatic connection, port 1 | Male thread G3/8 |
| Pneumatic connection, port 2 | Female thread G3/8 |
| Note on materials | RoHS-compliant |
| Material housing | Wrought aluminium alloy |
| Material shaft | High-alloy steel |