

Declaration of Performance

- | | |
|--|---|
| No.: | DoP KKplus s1 01092021001 |
| 1. Unique identification code of the product-type: | FEF Kaiflex KKplus s1 |
| 2. Intended use/es: | Thermal insulation for technical building equipment an industrial installations (ThIBEII) |
| 3. Manufacturer: | Kaimann GmbH
Hansastraße 2-5
D-33161 Hövelhof |
| 4. Authorised representative: | Not relevant |
| 5. System/s of AVCP | 1 |
| 6. a. Harmonised standard: | Declaration of performance according to product standard EN 14304:2009+A1:2013 |
| Notified body/ies: | 0751 "Forschungsinstitut für Wärmeschutz e.V. München" |
| b. European Assessment Document: | Not relevant |
| 7. Declared performance/s: | |

Essential Features		Performance				
Reaction to fire euroclass-characteristics	Reaction to fire	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	B-s1, d0 B _L -s1, d0			
Acoustic absorption index	Structure-borne noise transmission Acoustic absorption		NPD			
Thermal resistance	Thermal conductivity Dimensions and limits	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	°C	-10 °C	0 °C	10 °C
Water permeability	Water absorption		W/(m·K)	0,037	0,038*	0,039
Water vapour permeability	Water vapour diffusion resistance	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	WS01 (W _p ≤ 0,1 kg/m ²)			
Release of corrosive substances	Minor amounts of water soluble chlorides and pH-value		NPD			
Release of dangerous substances to indoor environment	Release of dangerous substances		NPD ^a			
Continuous glowing combustion	Continuous glowing combustion		NPD			
Durability of reaction to fire against ageing/degradation	Durability characteristics ^b					
Durability of thermal resistance against ageing/degradation	Durability characteristics ^c					
	Maximum service temperature	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	ST(+) 85 °C ST(+) 110 °C			
	Minimum service temperature	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	ST(-) -50 °C			
Durability of reaction to fire Against high temperature	Durability characteristics ^b					
Durability of thermal resistance against high temperature	Durability characteristics ^c					

^a No test method yet adopted.
^b The fire performance of flexible elastomeric foam does not change with time.
^c The thermal conductivity of flexible elastomeric foam does not change with time.
 NPD = No Performance Determined
^{*}λ_s ≤ 0,038 + 9,0144 · 10⁻⁵ θ + 3,29744 · 10⁻⁷ θ²

8. Appropriate Technical Documentation and/or Specific Technical Documentation: The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jesko Adler, CIO / Head of Quality



Hövelhof, 01.09.2021