


ISO 7380-1 A2

ISO 7380-1 A2 Flachrundkopfschrauben Innensechskant, Vollgewinde

ISO 7380-1 A2 Hexagon socket button head screws with fullthread



Auf Wunsch Fremdüberwacht
von M6 bis einschl. M12
lieferbar.
- "0" = reduzierte
Belastbarkeit

quality inspection from M6
including to M12 available on
demand.

- "0" = reduced load capacity

d	M 2	M 2,5	M 3	M 4	M 5
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
3	7380122 3	73801225 3	7380123 3		
4	7380122 4	73801225 4	7380123 4	7380124 4	
5	7380122 5	73801225 5	7380123 5	7380124 5	7380125 5
6	7380122 6	73801225 6	7380123 6	7380124 6	7380125 6
8	7380122 8	73801225 8	7380123 8	7380124 8	7380125 8
10	7380122 10	73801225 10	7380123 10	7380124 10	7380125 10
12	7380122 12	73801225 12	7380123 12	7380124 12	7380125 12
14	7380122 14	73801225 14	7380123 14	7380124 14	7380125 14
16	7380122 16	73801225 16	7380123 16	7380124 16	7380125 16
18			7380123 18	7380124 18	7380125 18
20	7380122 20	73801225 20	7380123 20	7380124 20	7380125 20
22			7380123 22	7380124 22	7380125 22
25			7380123 25	7380124 25	7380125 25
30			7380123 30	7380124 30	7380125 30
35			7380123 35	7380124 35	7380125 35
40			7380123 40	7380124 40	7380125 40
45			7380123 45	7380124 45	7380125 45
50			7380123 50	7380124 50	7380125 50
55				7380124 55	7380125 55
60				7380124 60	7380125 60
65					7380125 65
70					7380125 70
75					7380125 75
80					7380125 80
90					
100					
110					
120					

	1000	1000	1000 ≥ 35 500 ≥ 50 200	1000 ≥ 20 500 ≥ 35 200 ≥ 60 100	500 ≥ 25 200 ≥ 60 100
dk	3,4	4,6	5,7	7,6	9,5
k	1,3	1,5	1,65	2,2	2,75
t	0,6	0,7	1,04	1,3	1,56
Antrieb	SW 1,3	SW 1,5	SW 2	SW 2,5	SW 3