

DIN 933 A4-80
Sechskantschrauben mit Gewinde bis Kopf

DIN 933 A4-80
Hexagon head screws

DIN 933
A4-80
 Alternative Norm
 ersetzt durch ISO 4017

d	M 4	M 5	M 6	M 8
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
6	09334804 6			
8	09334804 8	09334805 8	09334806 8	
10	09334804 10	09334805 10	09334806 10	09334808 10
12	09334804 12	09334805 12	09334806 12	09334808 12
14	09334804 14	09334805 14	09334806 14	09334808 14
16	09334804 16	09334805 16	09334806 16	09334808 16
18	09334804 18	09334805 18	09334806 18	09334808 18
20	09334804 20	09334805 20	09334806 20	09334808 20
22	09334804 22	09334805 22	09334806 22	09334808 22
25	09334804 25	09334805 25	09334806 25	09334808 25
28				09334808 28
30	09334804 30	09334805 30	09334806 30	09334808 30
35	09334804 35	09334805 35	09334806 35	09334808 35
40	09334804 40	09334805 40	09334806 40	09334808 40
45	09334804 45	09334805 45	09334806 45	09334808 45
50	09334804 50	09334805 50	09334806 50	09334808 50
55	09334804 55	09334805 55	09334806 55	09334808 55
60	09334804 60	09334805 60	09334806 60	09334808 60
65	09334804 65	09334805 65	09334806 65	09334808 65
70	09334804 70	09334805 70	09334806 70	09334808 70
75	09334804 75	09334805 75	09334806 75	09334808 75
80	09334804 80	09334805 80	09334806 80	09334808 80
85		09334805 85	09334806 85	09334808 85
90		09334805 90	09334806 90	09334808 90
95		09334805 95	09334806 95	09334808 95
100		09334805 100	09334806 100	09334808 100
110			09334806 110	09334808 110
120			09334806 120	09334808 120
130			09334806 130	09334808 130
140			09334806 140	09334808 140
150			09334806 150	09334808 150
160			09334806 160	09334808 160
170			09334806 170	09334808 170
180			09334806 180	09334808 180
190			09334806 190	09334808 190
200			09334806 200	09334808 200



DIN

Auf Wunsch Fremdüberwacht
 von M6 bis einschl. M24
 lieferbar.

Weitere Abmessungen auf
 Anfrage lieferbar!
 - Zugfestigkeit 800 N/mm²

quality inspection from M6
 including to M24 available on
 demand.

Other dimensions on demand!
 - tensile strength 800 N/mm²

D	1000		500	
	>= 20		>= 14	
	500	500	200	500
	>= 35	>= 25	>= 45	>= 14
	200	200	100	200
	>= 60	>= 70	>= 120	>= 25
	100	100	50	100
			>= 130	>= 70
			100	50
			>= 140	
			50	
k	2,8	3,5	4	5,3
e	7,66	8,79	11,05	14,38
Antrieb	SW 7	SW 8	SW 10	SW 13