



P550335

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	76 mm (2.99 inch)
Thread Size	3/4-16
Length	86 mm (3.39 inch)
Gasket OD	70 mm (2.76 inch)
Gasket ID	60 mm (2.36 inch)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	0.75 bar (11 psi)
-------------------------	-------------------

Bypass Valve Setting HR	1.2 bar (17 psi)
-------------------------	------------------

Media Type	Cellulose
------------	-----------

Collapse Burst	6.9 bar (100 psi)
----------------	-------------------

Type	Full-Flow
------	-----------

Style	Spin-On
-------	---------

Packaged Dimensions

Packaged Length	3 IN
-----------------	------

Packaged Width	3 IN
----------------	------

Packaged Height	3.3IN
-----------------	-------

Packaged Weight	0.685 LB
-----------------	----------

Packaged Volume	0.0172 FT3
-----------------	------------

Other Information

Country of Origin	Colombia
-------------------	----------

NMFC Code	069100-10
-----------	-----------

HTS Code	8421230090
----------	------------

UPC Code	742330042236
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.