


ISO 4014 A4-80

Alternative Norm
ehemals DIN 931

ISO 4014 A4-80 Sechskantschrauben mit Schaft

ISO 4014 A4-80
Hexagon head bolts



b = nach Norm

Auf Wunsch Fremdüberwacht
von M6 bis einschl. M24
lieferbar.

b = at Norm

quality inspection from M6
including to M24 available on
demand.

d	M 5	M 6	M 8	M 10
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
25	40144805 25			
30	40144805 30	40144806 30	40144808 30	
35	40144805 35	40144806 35	40144808 35	401448010 35
40	40144805 40	40144806 40	40144808 40	401448010 40
45	40144805 45	40144806 45	40144808 45	401448010 45
50	40144805 50	40144806 50	40144808 50	401448010 50
55	40144805 55	40144806 55	40144808 55	401448010 55
60	40144805 60	40144806 60	40144808 60	401448010 60
65	40144805 65	40144806 65	40144808 65	401448010 65
70	40144805 70	40144806 70	40144808 70	401448010 70
75	40144805 75	40144806 75	40144808 75	401448010 75
80		40144806 80	40144808 80	401448010 80
85		40144806 85	40144808 85	401448010 85
90		40144806 90	40144808 90	401448010 90
95		40144806 95	40144808 95	401448010 95
100		40144806 100	40144808 100	401448010 100
110		40144806 110	40144808 110	401448010 110
120		40144806 120	40144808 120	401448010 120
130		40144806 130	40144808 130	401448010 130
140		40144806 140	40144808 140	401448010 140
150		40144806 150	40144808 150	401448010 150
160			40144808 160	401448010 160
170				401448010 170
180				401448010 180
190				401448010 190
200				401448010 200
210				401448010 210
220				401448010 220
230				401448010 230
240				401448010 240
250				401448010 250

	200 ≥ 70 100	200 ≥ 45 100	100 ≥ 70 50 ≥ 160 25	100 ≥ 110 50 ≥ 160 25
k	3,5	4	5,3	6,4
Antrieb	SW 8	SW 10	SW 13	SW 16