



2315 LED

LED Water-proof luminaire

- Simple installation
- Flexible mounting options
- Adjustable luminaire luminous flux

The 2315 LED is the ideal weather-proof luminaire for e.g. multi-storey car parks, storage areas, production areas and canopied outdoor areas. As an ideal 1:1 LED refurbishment solution with multi-lumen technology, it can be mounted to walls and ceilings, can be suspended, is very robust and also easy and flexible to install. This will get the job done!

Why you'll master the job with the 2315 LED weather-proof luminaire

- Rapid connection system with tool-free bayonet catch reduces installation effort.
- Thanks to slidable mounting clips, can be individually adapted to the existing fixing points.
- Variants available with integrated through-wiring.
- Suitable for wall, ceiling and suspended mounting.
- UV-stabilised polycarbonate – robust and reliable.
- High efficiency (126 lm/W) and reliable service life (50,000 h, L65)
- Flexible luminous flux setting thanks to multi-lumen function (3,800 lm and 2,600 lm or 5,600 lm and 3,800 lm)

2315 LED at a glance

Dimensions (L x W x H):	1,200: 1,235 x 64 x 65 mm 1,500: 1,535 x 64 x 65 mm
Version with through-wiring (+LV):	L= 1,270 / 1,570 mm
Luminaire luminous flux:	1,200: 3,800 lm, 2,600 lm 1,500: 5,600 lm, 3,800 lm
Colour rendering/-temperature:	Ra>80 / 4,000 K
Connected load:	47 / 30 W, 32 / 22 W
Protection rating, safety class:	IP65, SK I
Weight:	1,200: 0,9 kg 1,500: 1,1 kg

All versions of 2315 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
Multilumen (adjustable luminaire luminous flux)						
2315 G3 1200 38/26/ML-840 ET PC	7756440	3800 / 2600	32 / 22	4000	1235 x 64 x 65	1 x 36 W 2 x 36 W
2315 G3 1500 55/38/ML-840 ET PC	7756540	5600 / 3800	47 / 30	4000	1535 x 64 x 65	1 x 58 W 2 x 58 W
Multilumen (adjustable luminaire luminous flux) with through-wiring						
2315 G3 1200 38/26/ML-840 ET PC +LV	7756640	3800 / 2600	32 / 22	4000	1270 x 64 x 65	1 x 36 W 2 x 36 W
2315 G3 1500 55/38/ML-840 ET PC +LV	7756740	5600 / 3800	47 / 30	4000	1570 x 64 x 65	1 x 58 W 2 x 58 W