

# 2350 LED

## LED surface-mounted luminaire

- Pleasant light effect due to uniform illumination
- VDU workstation-compliant (UGR < 19)
- Adjustable light colour and luminous intensity

The 2350 LED surface-mounted luminaire is the clever solution for standard-compliant illumination in e.g. offices, corridors, foyers, conference rooms, sales areas, waiting zones, educational, health and care facilities. With three sizes and flexible luminous flux packages, the right lighting solution is available for any type of room. This will get the job done!

### Why you'll master the job with the 2350 LED surface-mounted luminaire

- Flexible setting of luminaire luminous flux due to multilumen
- Thanks to Multicolour, two light colours in one luminaire.
- 1:1 replacement of conventional luminaires during refurbishment.
- Quick and easy mounting saves time.
- Pleasant light effect due to uniform illumination, suitable for VDU workstations (UGR < 19).
- High efficiency (up to 111 lm/W) and reliable service life (50,000 h, L65)

### 2350 LED at a glance

<b>Dimensions:</b>	D: 625 x 625 x 46 mm D2: 1225 x 325 x 46 mm D3: 1525 x 325 x 46 mm
<b>Luminaire luminous flux:</b>	D: 3.600 / 2.900 lm (Multilumen) D2: 4.000 lm, 3.000 lm (Multilumen) D3: 6.000 lm, 4.000 lm (Multilumen)
<b>Colour rendering/-temperature:</b>	Ra > 80 / 4000K, 3000 & 4000K (multi-color)
<b>Connected load:</b>	D: 25W / 33W D2: 30W / 36W D3: 38W / 54W
<b>Protection rating, safety class:</b>	IP20 / IK02 / I
<b>Weight:</b>	D: 2,8 kg; D2: 3,4 kg; D3: 4,2kg
<b>Light management:</b>	LiveLinkReady (ETDD) Wireless Connect (ETWD)

### All versions of 2350 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions L×W×H [mm]	Replacement
<b>Square version</b>						
<b>Multi-colour / multi-lumen (light colour and luminous flux adjustable)</b>						
2350 G3 D PW19 36/29/ML-8MC ET	7640840	3600 / 2900	33 / 25	4000 / 3000	625 x 625 x 46	3 x 14 W / 4 x 14 W / 3 x 18 W / 4 x 18 W
<b>Wireless Connect / Multi-color</b>						
2350 G3 D PW19 3600-8MC ETWD	7938265	3600	33	4000 / 3000	625 x 625 x 46	3 x 14 W / 4 x 14 W / 3 x 18 W / 4 x 18 W
<b>Rectangular version</b>						
<b>Multilumen (adjustable luminaire luminous flux)</b>						
2350 G3 D2 PW19 40/30/ML-840 ET	7755740	4000 / 3000	36 / 30	4000	1225 x 325 x 46	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G3 D2 PW19 40/30/ML-8MC ET	7755640	4000 / 3000	36 / 30	4000 / 3000	1225 x 325 x 46	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G3 D3 PW19 60/40/ML-840 ET	7756140	6000 / 4000	54 / 38	4000	1525 x 325 x 46	2 x 28 W / 2 x 35 W / 2 x 58 W
2350 G3 D3 PW19 60/40/ML-8MC ET	7756040	6000 / 4000	54 / 38	4000 / 3000	1525 x 325 x 46	2 x 28 W / 2 x 35 W / 2 x 58 W
<b>DALI / Multi-colour</b>						
2350 G3 D2 PW19 4000-840 ETDD	7755951	4000	36	4000	1225 x 325 x 46	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G3 D2 PW19 4000-8MC ETDD	7755851	4000	36	4000 / 3000	1225 x 325 x 46	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G3 D3 PW19 6000-840 ETDD	7756351	6000	54	4000	1525 x 325 x 46	2 x 28 W / 2 x 35 W / 2 x 58 W
2350 G3 D3 PW19 6000-8MC ETDD	7756251	6000	54	4000 / 3000	1525 x 325 x 46	2 x 28 W / 2 x 35 W / 2 x 58 W
<b>Wireless Connect / Multi-color</b>						
2350 G3 D2 PW19 4000-8MC ETWD	7916465	4000	36	4000 / 3000	1225 x 325 x 46	2 x 28 W / 1 x 49 W / 1 x 58 W
2350 G3 D3 PW19 4400-8MC ETWD	7916665	4400	40	4000 / 3000	1525 x 325 x 46	2 x 28 W / 2 x 35 W / 2 x 58 W