



2310 LED

LED Water-proof luminaire

- Wide distribution optic
- Refurbishment-friendly
- Adjustable luminaire luminous flux

The 2310 LED is the ideal weatherproof luminaire for e.g. multi-storey car parks, storage areas, production areas and canopied outdoor areas. The multi-lumen function, a variety of feed points and easy installation make it the ideal solution for one-to-one LED refurbishments. The possibility of replacing individual components at a later date provides it with a particularly long service life. This will get the job done!

Why you'll get the job done with the 2310 LED weatherproof luminaire

- Optimally suited for any lighting task due to wide distribution optic.
- Openability of the luminaire allows subsequent replacement of components and power supply via the rear of the luminaire.
- Can be flexibly positioned with up to 11 feed points and sliding mounting clips.
- Suitable for wall, ceiling and suspended mounting. Through-wiring as an accessory.
- Diffuser available in PC and PMMA materials.
- High efficiency (up to 122 lm/W) and reliable service life (50,000 h, L65)
- Flexible luminous flux setting thanks to multi-lumen function (6,000 lm and 4,000 lm)

2310 LED at a glance

Dimensions (L x W x H):	1200: 1257 x 102 x 91 mm 1500: 1552 x 102 x 91 mm
Luminaire luminous flux:	1200: 4,000 lm 1500: 6,000 lm, 4,000 lm (Multilumen)
Colour Rendering Index:	Ra > 80
Colour Temperature:	4000 K
Connected load:	33 W, 33 / 23 W
Protection rating, safety class:	IP66 / IK08, I
Weight:	1200: 2.3 kg 1500: 2.6 kg

All versions of 2310 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions L×W×H [mm]	Replacement
Switchable						
2310 12 B 40-840 ET PC	7922740	4000	35	4000	1257 × 102 × 91	1 × 36 W / 2 × 36 W
2310 12 B 40-840 ET	7922840	4000	35	4000	1257 × 102 × 91	1 × 36 W / 2 × 36 W
Multilumen (adjustable luminaire luminous flux)						
2310 15 B 40/60/ML-840 ET PC	7922940	6000 / 4000	49 / 35	4000	1552 × 102 × 91	1 × 58 W / 2 × 58 W
2310 15 B 40/60/ML-840 ET	7923040	6000 / 4000	49 / 35	4000	1552 × 102 × 91	1 × 58 W / 2 × 58 W

Parts for 2310 LED

Product reference	TOC	Description	Dimensions L×W×H [mm]	Weight
2310 ZLV/525/12	7923100	Through-wiring, 5-core 2.5 mm ²	1257 × 102 × 91	0,2 kg
2310 ZLV/525/15	7923200	Through-wiring, 5-core 2.5 mm ²	1552 × 102 × 91	0,2 kg