


ISO 4027 A4
Gewindestifte mit Innensechskant und Spitze

ISO 4027 A4
Hexagon socket set screws with cone point

ISO 4027
A4

Alternative Norm
ehemals DIN 914

d	M 2	M 2,5	M 3	M 4	M 5	M 6
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2	402742 2					
3	402742 3	4027425 3	402743 3	402744 3		
4	402742 4	4027425 4	402743 4	402744 4	402745 4	
5	402742 5	4027425 5	402743 5	402744 5	402745 5	402746 5
6	402742 6	4027425 6	402743 6	402744 6	402745 6	402746 6
8	402742 8	4027425 8	402743 8	402744 8	402745 8	402746 8
10	402742 10	4027425 10	402743 10	402744 10	402745 10	402746 10
12	402742 12	4027425 12	402743 12	402744 12	402745 12	402746 12
14	402742 14	4027425 14	402743 14	402744 14	402745 14	402746 14
16	402742 16	4027425 16	402743 16	402744 16	402745 16	402746 16
18			402743 18	402744 18	402745 18	402746 18
20			402743 20	402744 20	402745 20	402746 20
22						402746 22
25			402743 25	402744 25	402745 25	402746 25
30			402743 30	402744 30	402745 30	402746 30
35			402743 35	402744 35	402745 35	402746 35
40			402743 40	402744 40	402745 40	402746 40
45				402744 45	402745 45	402746 45
50				402744 50	402745 50	402746 50
55					402745 55	402746 55
60					402745 60	402746 60
70						402746 70
80						402746 80
90						
100						
120						



	500	500	500 ≥ 30 200	500 ≥ 30 200	500 ≥ 25 200	200
dt	0,5	0,65	0,75	1	1,25	1,5
Antrieb	SW 0,9	SW 1,3	SW 1,5	SW 2	SW 2,5	SW 3

ISO