



Product Specifications



P553191

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1 1/8-16 UN
Length	262 mm (10.31 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	90 mm (3.54 inch)
Efficiency 99%	21 micron
Efficiency Test Std	ISO 16889
Media Type	Cellulose
Collapse Burst	10.3 bar (149 psi)

Type	Full-Flow
Style	Spin-On
Primary Application	up to EURO4 applications, for EURO5/6 use P551807

Packaged Dimensions

Packaged Length	4.35 IN
Packaged Width	4.35 IN
Packaged Height	10.45IN
Packaged Weight	2.605 LB
Packaged Volume	0.1144 FT3

Other Information

Country of Origin	Poland
NMFC Code	069095-02
HTS Code	84212300 90
UPC Code	742330044308

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.