



## P550008

### LUBE FILTER, SPIN-ON FULL FLOW

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

#### Attributes

Outer Diameter	95 mm (3.74 inch)
Thread Size	3/4-16 UN
Length	136 mm (5.35 inch)
Gasket OD	72.4 mm (2.85 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	0.5 bar (7 psi)
Bypass Valve Setting HR	0.7 bar (10 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On

---

#### Packaged Dimensions

Packaged Length	10.0584 M3
Packaged Width	10.0584 M3
Packaged Height	14.3256M3
Packaged Weight	0.6078137758 KG
Packaged Volume	0.0014696443 M3

---

#### Other Information

Country of Origin	Türkiye
NMFC Code	069095-02
HTS Code	8421230090
UPC Code	742330040119

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.