

DALLAS EXPRESS LED BACKLIT PANEL

20W/28W/32W, IP20






PRODUCT INFORMATION DOCUMENT

FEATURES

- The new DALLAS EXPRESS is our first multiwattage panel range allowing to select between three powers and lumen outputs to suit any application requirements
- Allows compliance with project requirements for Low Glare in offices or classrooms and all other parts of the building.
- Available as UGR<22 and UGR<19
- Very high efficacy exceeding 130 lumens per circuit watt
- Emergency pack available providing high lumen light output on mains failure
- Includes mounting point for a safety strap
- Uses Backlit luminaire construction design

CONSTRUCTION

- White powder coated aluminium frame
- Polystyrene TPa rated diffuser



Product Code:	RDLX4060	RDLX4060E	RDLX5060	RDLX4060UGR	RDLX4060UGRE	RDLX5060UGR
Standard Emergency						
Comparable to:	4x18W T8	4x18W T8	4x18W T8	4x18W T8	4x18W T8	4x18W T8
Total Power (W):	19.5/27.3/31.6	19.5/27.3/31.6	19.5/27.4/31.6	19.4/27.4/31.7	19.4/27.3/31.6	20.3/28.2/32.6
Power Factor:	0.9	0.9	0.9	0.9	0.9	0.9
Total Light Output (lm):	2730/3800/4320	2730/3800/4320	2690/3760/4250	2700/3760/4260	2700/3760/4270	2660/3200/3620
Total Emergency Light Output (lm):	NA	NA	NA	NA	NA	NA
Efficacy (lm/cctW):	140/139/136	138/137/134	138/137/134	140/137/135	140/137/135	131/129/126
Beam Angle (deg):	110	110	110	90	90	90
Lux at 1m (lux):	930/1400/1470	930/1400/1470	910/1270/1440	1250/1740/1970	1250/1740/1970	1240/1690/1910
Emergency Lux at 1m (lux):	NA	NA	NA	NA	NA	NA
CCT (K):	4000	4000	5000	4000	4000	5000
CRI:	80	80	80	80	85	80
IP:	20	20	20	20	20	20
Operation Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Inrush Current:	7.76A/38us	7.76A/38us	7.76A/38us	6.6A/12us	6.6A/12us	6.6A/12us
RG Value:	0	0	0	0	0	0
SDCM:	6	6	6	6	6	6
Energy Class:	C	C	C	C	C	C
Rated Life to L70B50 (Hrs):	125000	125000	125000	125000	125000	125000
Rated Life to L80B10 (Hrs):	72000	72000	72000	72000	72000	72000
Rated Life to L90B10 (Hrs):	37000	37000	37000	37000	37000	37000
Dimensions LxWxH (mm):	595x595x34	595x595x34	595x595x34	595x595x34	595x595x34	595x595x34
Weight (kg):	1.37	1.42	1.37	1.63	1.66	1.63

Separate Control Gear Information

Type of Light Source:	LED	LED	LED	LED	LED	LED
Full Load Efficiency (%):	89	89	89	89	89	89
P _{NET} (W):	NA	NA	NA	NA	NA	NA
Dimensions (mm):	170x40x25	170x40x25	170x40x25	170x40x25	170x40x25	170x40x25

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM
WEB: ROBUS.COM
WEB: ROBUS.COM.AU
WEB: ROBUSLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

DALLAS EXPRESS LED
BACKLIT PANEL
20W/28W/32W, IP20

Cone Illuminance Diagram





Diagram for RDLX5060UGR-01 at 32W. Other diagrams available on request


Dimension Diagram



Sensor Data

Time Off Delay:	NA
Illuminance Switching Range:	NA
Sensitivity Range (%):	NA
Mounting Height (max):	NA
Detection Zone Diameter (max):	NA

Polar Intensity Diagram



Accessories

R3EMPK4-PSU	3 Hour Emergency Pack with LiFePO4 Battery
HED2040-D	1-10V, DALI and Push dim driver available
RDLSST	Safety Strap kit for DALLAS Panels
RDL6060SF-01	Surface Mount Box Kit for 600x600 panel
	White 70mm deep Flat Pack
RDLSUS-4W	1.5m Stainless Steel Suspension Kit

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE