

ISO 4029

A2


Alternative Norm
ehemals DIN 916

ISO 4029 A2

Gewindestifte mit Innensechskant und Ringschneide

ISO 4029 A2

Hexagon socket set screws with cup point



d	M 6	M 8	M 10	M 12	M 16	M 20
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2						
3						
4						
5	402926 5					
6	402926 6	402928 6	4029210 6			
8	402926 8	402928 8	4029210 8	4029212 8		
10	402926 10	402928 10	4029210 10	4029212 10		
12	402926 12	402928 12	4029210 12	4029212 12		
14	402926 14	402928 14	4029210 14	4029212 14	4029216 14	
16	402926 16	402928 16	4029210 16	4029212 16	4029216 16	
18	402926 18	402928 18	4029210 18	4029212 18	4029216 18	
20	402926 20	402928 20	4029210 20	4029212 20	4029216 20	4029220 20
25	402926 25	402928 25	4029210 25	4029212 25	4029216 25	4029220 25
30	402926 30	402928 30	4029210 30	4029212 30	4029216 30	4029220 30
35	402926 35	402928 35	4029210 35	4029212 35	4029216 35	4029220 35
40	402926 40	402928 40	4029210 40	4029212 40	4029216 40	4029220 40
45	402926 45	402928 45	4029210 45	4029212 45	4029216 45	4029220 45
50	402926 50	402928 50	4029210 50	4029212 50	4029216 50	4029220 50
55	402926 55	402928 55	4029210 55	4029212 55	4029216 55	4029220 55
60	402926 60	402928 60	4029210 60	4029212 60	4029216 60	4029220 60
70	402926 70	402928 70	4029210 70	4029212 70	4029216 70	4029220 70
80	402926 80	402928 80	4029210 80	4029212 80	4029216 80	4029220 80
90		402928 90	4029210 90	4029212 90	4029216 90	4029220 90
100		402928 100	4029210 100	4029212 100	4029216 100	4029220 100
120		402928 120	4029210 120	4029212 120		

	200	200	200 >= 25 100	100 >= 70 50	50 >= 80 25	50 >= 70 25
dv	3	5	6	8	10	14
Antrieb	SW 3	SW 4	SW 5	SW 6	SW 8	SW 10