

# Push-in T-connector NPQP-T-Q10-Q8-FD-P10

Part number: 133117

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                  | Value                                     |
|--|---|
| Size                                     | Standard                                  |
| Nominal size                             | 5 mm                                      |
| Design                                   | T-shape                                   |
| Size of pack                             | 10  |
| Design                                   | Push-pull principle                       |
| Temperature-dependent operating pressure | -0.95 bar ... 10 bar                      |
| Operating medium                         | Compressed air to ISO 8573-1:2010 [7::-:] |
| Note on operating and pilot medium       | Lubricated operation possible             |
| Corrosion resistance class CRC           | 4 - Very high corrosion stress            |
| LABS (PWIS) conformity                   | VDMA24364 zone III                        |
| Suitable for use with food               | See supplementary material information    |
| Ambient temperature                      | -20 °C ... 60 °C                          |
| Product weight                           | 19.5 g                                    |
| Pneumatic connection, port 1             | For tubing outer diameter of 10 mm        |
| Pneumatic connection, port 2             | For tubing outside diameter of 8 mm       |
| Note on materials                        | RoHS-compliant                            |
| Material housing                         | PP  |
| Material tubing clamp component          | High-alloy stainless steel                |