


ISO 4029 A4
Gewindestifte mit Innensechskant und Ringschneide

ISO 4029 A4
Hexagon socket set screws with cup point

ISO 4029
A4
Alternative Norm
ehemals DIN 916

d	M 1,6	M 2	M 2,5	M 3	M 4	M 5
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2	4029416 2	402942 2				
3	4029416 3	402942 3	4029425 3	402943 3	402944 3	
4	4029416 4	402942 4	4029425 4	402943 4	402944 4	402945 4
5	4029416 5	402942 5	4029425 5	402943 5	402944 5	402945 5
6	4029416 6	402942 6	4029425 6	402943 6	402944 6	402945 6
8	4029416 8	402942 8	4029425 8	402943 8	402944 8	402945 8
10		402942 10	4029425 10	402943 10	402944 10	402945 10
12		402942 12	4029425 12	402943 12	402944 12	402945 12
14		402942 14	4029425 14	402943 14	402944 14	402945 14
16		402942 16	4029425 16	402943 16	402944 16	402945 16
18				402943 18	402944 18	402945 18
20				402943 20	402944 20	402945 20
25				402943 25	402944 25	402945 25
30				402943 30	402944 30	402945 30
35				402943 35	402944 35	402945 35
40				402943 40	402944 40	402945 40
45					402944 45	402945 45
50					402944 50	402945 50
55						402945 55
60						402945 60
70						
80						
90						
100						
120						



	200	500	500	500 ≥ 30 200	500 ≥ 30 200	500 ≥ 25 200
dv	0,8	1	1,2	1,4	2	2,5
Antrieb	SW 0,7	SW 0,9	SW 1,3	SW 1,5	SW 2	SW 2,5

ISO