

BSP **DRAADFITTINGEN - UIT BUIS**
BSP ***THREADED FITTINGS - FROM PIPE***


Draad volgens ISO 7-1R: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to ISO 7-1R: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

SOK UIT BUIS



SOCKET FROM PIPE




INCH	NW	D	L	304L	316L
1/8"	6	14,0	20	O	X
¼"	8	18,5	25	X	X
3/8"	10	21,5	26	X	X
½"	15	26,5	34	X	X
¾"	20	32,0	36	X	X
1"	25	39,5	43	X	X
1 ¼"	32	48,5	48	X	X
1 ½"	40	54,5	48	X	X
2"	50	66,5	56	X	X
2 ½"	65	82,0	65	O	X
3"	80	95,0	71	O	X
4"	100	122,0	83	O	X

HALVE SOK UIT BUIS



HALF SOCKET FROM PIPE



INCH	NW	D	L	304L	316L
1/8"	6	14,0	11	O	X
¼"	8	18,5	13	X	X
3/8"	10	21,5	12	X	X
½"	15	26,5	15	X	X
¾"	20	32,0	17	X	X
1"	25	39,5	19	X	X
1 ¼"	32	48,5	22	X	X
1 ½"	40	54,5	22	X	X
2"	50	66,5	26	X	X
2 ½"	65	82,0	30	O	X
3"	80	95,0	33	O	X
4"	100	122,0	40	O	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - UIT BUIS**
BSP ***THREADED FITTINGS - FROM PIPE***

Draad volgens ISO 7-1R: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to ISO 7-1R: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

LASNIPPEL UIT BUIS



WELDING NIPPLE FROM PIPE



INCH	1/8"	¼"	3/8"	½"	¾"	1"	1 ¼"	1 ½"	2"	2 ½"	3"	4"	5"	6"
NW	6	8	10	15	20	25	32	40	50	65	80	100	125	150
D	10,2	13,5	17,2	21,3	26,9	33,7	42,4	48,3	60,3	76,1	88,9	114,3	139,7	168,3
D1	10,0	13,5	17,0	21,0	27,0	33,5	42,0	48,0	60,5	76,0	89,0	114,0		
L = 18 MM	O	X	O	O	O	O	O	O	O	O	O	O	O	O
L = 30 MM	X	X+304L	X+304L	O	O	O	O	O	O	O	O	O	O	O
L = 35 MM	O	O	X	X+304L	O	O	O	O	O	O	O	O	O	O
L = 40 MM	O	X	X	X	X+304L	X+304L	O	O	O	O	O	O	O	O
L = 50 MM	O	X	X	X	X	X	X+304L	X+304L	X+304L	O	O	O	O	O
L = 60 MM	O	X	X	X	X	X	X	X	X	X	O	O	O	O
L = 70 MM	O	X	X	X	X	X	X	X	X	O	X	O	O	O
L = 80 MM	X	X	X	X	X	X	X	X	X	O	O	X	O	O
L = 90 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 100 MM	O	X	X	X	X	X	X	X	X	O	O	O	1.4571	O
L = 110 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 120 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	1.4571
L = 130 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 140 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 150 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 160 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 170 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 180 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 190 MM	O	O	O	X	O	O	O	O	O	O	O	O	O	O
L = 200 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 210 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 220 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 230 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 240 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 250 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 260 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 270 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 280 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 290 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 300 MM	O	X	X	X	X	X	X	X	O	O	O	O	O	O

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - UIT BUIS**
BSP ***THREADED FITTINGS - FROM PIPE***


Draad volgens ISO 7-1R: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to ISO 7-1R: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

PIJPNIPPEL UIT BUIS



BARREL NIPPLE FROM PIPE



INCH	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
NW	6	8	10	15	20	25	32	40	50	65	80	100	125	150
D	10,2	13,5	17,2	21,3	26,9	33,7	42,4	48,3	60,3	76,1	88,9	114,3	139,7	168,3
L = 30 MM	O	X	O	X	O	O	O	O	O	O	O	O	O	O
L = 40 MM	X	X+304L	X+304L	X	X	X	O	O	O	O	O	O	O	O
L = 50 MM	O	X	X	X	X	X	O	O	O	O	O	O	O	O
L = 60 MM	O	X	X	X+304L	X+304L	X+304L	X	X	O	O	O	O	O	O
L = 70 MM	O	X	X	X	X	O	X	X	O	O	O	O	O	O
L = 80 MM	O	X	X	X	X	X	X+304L	X+304L	X	O	O	O	O	O
L = 90 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 100 MM	O	X	X	X	X	X	X	X	X+304L	X	O	O	O	O
L = 110 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 120 MM	O	X	X	X	X	X	X	X	X	O	X	X	O	O
L = 130 MM	O	O	X	X	X	O	X	X	X	O	O	O	O	O
L = 140 MM	O	X	X	X	X	O	X	X	X	O	O	O	O	O
L = 150 MM	O	X	X	X	X	X	X	X	X	O	O	O	1.4571	1.4571
L = 160 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 170 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 180 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 190 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 200 MM	O	X	X	X	X	X	X	X	X	O	O	O	O	O
L = 210 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 220 MM	O	X	X	X	X	X	O	X	X	O	O	O	O	O
L = 230 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 240 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 250 MM	O	O	X	X	X	X	X	X	X	O	O	O	O	O
L = 260 MM	O	O	O	O	O	O	O	X	O	O	O	O	O	O
L = 270 MM	O	O	O	O	O	O	O	O	O	O	O	O	O	O
L = 280 MM	O	O	O	O	O	O	O	X	O	O	O	O	O	O
L = 290 MM	O	O	O	O	O	O	O	X	O	O	O	O	O	O
L = 300 MM	O	O	O	X	X	X	X	X	X	O	O	O	O	O

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - UIT BUIS**
BSP ***THREADED FITTINGS - FROM PIPE***


Draad volgens ISO 7-1R: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to ISO 7-1R: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

BOCHT 90° BU / BU UIT BUIS



BEND 90° M / M FROM PIPE




INCH	NW	D	L	R	304L	316L
1/8"	6	10,2	50	30	O	X
¼"	8	13,5	60	40	O	X
3/8"	10	17,2	70	45	O	X
½"	15	21,3	80	55	O	X
¾"	20	26,9	100	70	O	X
1"	25	33,7	120	80	O	X
1.¼"	32	42,4	140	95	O	X
1.½"	40	48,3	160	115	O	X
2"	50	60,3	190	125	O	X
2.½"	65	76,1	240	170	O	O
3"	80	88,9	290	200	O	O

DRAADNIPPEL UIT BUIS



PARALELL NIPPLE FROM PIPE




INCH	NW	D	L	304L	316L
1/8"	6	10,2	16	O	X
¼"	8	13,5	18	O	X
3/8"	10	17,2	22	O	X
½"	15	21,3	25	O	X
¾"	20	26,9	30	O	X
1"	25	33,7	35	O	X
1 ¼"	32	42,4	38	O	X
1 ½"	40	48,3	38	O	X
2"	50	60,3	45	O	X
2 ½"	65	76,1	55	O	X
3"	80	88,9	60	O	X
4"	100	114,3	70	O	O

SLANGNIPPEL SLANG / BU



HOSE NIPPEL HOSE / M




INCH	NW	D	D1	L	L1	L2	316L (1.4408)
1/8"	6	10,2	8,62	70	30	12	X
¼"	8	13,5	11,92	70	30	12	X
3/8"	10	17,2	15,62	70	30	15	X
½"	15	21,3	19,45	75	35	20	X
¾"	20	26,7	25,05	75	35	20	X
1"	25	33,4	31,59	80	37,5	20	X
1 ¼"	32	42,2	39,76	90	40	25	X
1 ½"	40	48,3	45,67	90	40	25	X
2"	50	60,3	57,39	95	40	25	X
2 ½"	65	76,1	72,67	105	60	30	X
3"	80	88,9	85,23	110	60	30	X
4"	100	114,3	110,34	115	60	35	O

SLANGNIPPEL SLANG / LAS



HOSE NIPPEL HOSE / BW



INCH	NW	D	D1	L	L1	L2	316L (1.4408)
1/8"	6	10,2	8,62	70	30	12	X
¼"	8	13,5	11,92	70	30	12	X
3/8"	10	17,2	15,62	70	30	15	X
½"	15	21,3	19,45	75	35	20	X
¾"	20	26,7	25,05	75	35	20	X
1"	25	33,4	31,59	80	37,5	20	X
1.¼"	32	42,2	39,76	90	40	25	X
1.½"	40	48,3	45,67	90	40	25	X
2"	50	60,3	57,39	95	40	25	X
2.½"	65	76,1	72,67	105	60	30	X
3"	80	88,9	85,23	110	60	30	X
4"	100	114,3	110,34	115	60	35	O

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

T-STUK



EQUAL TEE




INCH	NW	D	L	304L (1.4308)	316L (1.4408)
1/8"	6	15,5	17,5	O	X
1/4"	8	19,0	19,5	X	X
3/8"	10	22,5	23,5	X	X
1/2"	15	27,5	27,5	X	X
3/4"	20	33,0	32,5	X	X
1"	25	40,5	38,5	X	X
1 1/4"	32	50,0	45,5	X	X
1 1/2"	40	56,5	48,5	X	X
2"	50	70,0	57,5	X	X
2 1/2"	65	86,5	69,5	O	X
3"	80	100,0	78,5	O	X
4"	100	126,0	96,5	O	X

KRUISSTUK



CROSS




INCH	NW	D	L	304L (1.4308)	304L (1.4408)
1/8"	6	15,5	17,5	O	X
1/4"	8	19,0	19,5	X	X
3/8"	10	22,5	23,5	X	X
1/2"	15	27,0	27,5	X	X
3/4"	20	32,5	32,5	X	X
1"	25	40,0	38,5	X	X
1 1/4"	32	50,0	45,5	X	X
1 1/2"	40	56,5	48,5	X	X
2"	50	69,0	57,5	X	X
2 1/2"	65	86,5	69,5	O	X
3"	80	100,0	78,5	O	X
4"	100	126,0	96,5	O	X

VERLOOP T-STUK BI / BI / BI



REDUCING TEE F / F / F



INCH X INCH	NW X NW	D1	D2	L1	L2	316L (1.4408)
1/4" X 1/8"	8 X 6	15,5	19,0	18,5	18,5	X
3/8" X 1/8"	10 X 6	15,5	22,5	19,5	20,5	X
3/8" X 1/4"	10 X 10	19,0	22,5	20,5	22,5	X
1/2" X 1/8"	15 X 6	15,5	27,5	23,5	23,5	X
1/2" X 1/4"	15 X 8	19,0	27,5	24,5	24,5	X
1/2" X 3/8"	15 X 10	22,5	27,5	26,5	25,5	X
3/4" X 1/4"	20 X 8	19,0	33,0	26,5	27,5	X
3/4" X 3/8"	20 X 10	22,5	33,0	28,5	28,5	X
3/4" X 1/2"	20 X 15	27,5	33,0	29,5	30,5	X
1" X 1/4"	25 X 8	19,0	40,5	27,5	30,5	X
1" X 3/8"	25 X 10	22,5	40,5	30,5	32,0	X
1" X 1/2"	25 X 15	27,5	40,5	32,5	33,5	X
1" X 3/4"	25 X 20	33,0	40,5	34,5	35,5	X
1 1/4" X 3/8"	32 X 10	22,5	50,0	34,0	36,5	X
1 1/4" X 1/2"	32 X 15	27,5	50,0	36,0	38,5	X
1 1/4" X 3/4"	32 X 20	33,0	50,0	38,5	40,5	X
1 1/4" X 1"	32 X 25	40,5	50,0	40,5	42,5	X
1 1/2" X 3/8"	40 X 10	22,5	56,5	34,0	40,0	X
1 1/2" X 1/2"	40 X 15	27,5	56,5	36,0	41,5	X
1 1/2" X 3/4"	40 X 20	33,0	56,5	38,5	43,5	X
1 1/2" X 1"	40 X 25	40,5	56,5	41,5	45,5	X
1 1/2" X 1 1/4"	40 X 32	50,0	56,5	45,5	48,5	X
2" X 1/2"	50 X 15	27,5	69,0	39,0	47,5	X
2" X 3/4"	50 X 20	33,0	69,0	41,5	49,5	X
2" X 1"	50 X 25	40,0	69,0	44,5	51,5	X
2" X 1 1/4"	50 X 32	50,0	70,0	48,5	54,5	X
2" X 1 1/2"	50 X 40	56,5	70,0	52,5	55,5	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***

Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

Y-STUK



Y-TEE




INCH	DN	D	L	L1	316L (1.4408)
1/8"	6	17,0	10,0	17,0	X
¼"	8	21,0	13,0	19,0	X
3/8"	10	25,0	14,0	23,0	X
½"	15	29,0	18,0	27,0	X
¾"	20	35,0	20,0	32,0	X
1"	25	43,0	23,0	38,0	X
1 ¼"	32	52,0	28,0	46,0	X
1 ½"	40	58,0	30,0	48,0	X
2"	50	71,0	34,0	57,0	X
2 ½"	65	88,0	40,0	68,0	X
3"	80	101,0	45,0	78,0	X
4"	100	129,0	52,0	97,0	X

KNIE MET STRIP BI / BI



ELBOW WITH BAR F / F




INCH	NW	DEGR	L	304L (1.4308)	316L (1.4408)
½"	15	45°	22,8	X	X
½"	15	60°	25,6	X	X
½"	15	75°	28,5	X	X
½"	15	90°	27,7	X	X

KNIE 45° BI / BI



ELBOW 45° F / F




INCH	NW	D	L	304L (1.4308)	316L (1.4408)
1/8"	6	15,5	16,5	O	X
¼"	8	19,0	17,5	X	X
3/8"	10	22,5	19,5	X	X
½"	15	27,0	21,5	X	X
¾"	20	32,5	25,5	X	X
1"	25	40,0	29,5	X	X
1 ¼"	32	50,0	33,5	X	X
1 ½"	40	56,5	37,5	X	X
2"	50	69,0	42,5	X	X
2 ½"	65	86,5	49,5	O	X
3"	80	100,0	54,5	O	X
4"	100	126,0	64,5	O	X

KNIE 45° BI / BU



STREET ELBOW 45° M / F



INCH	NW	D	L	L1	304L (1.4308)	316L (1.4408)
1/8"	6	17,0	16,0	21,0	O	X
¼"	8	21,0	17,0	23,0	X	X
2/8"	10	25,0	19,0	27,0	X	X
½"	15	29,0	21,0	31,0	X	X
¾"	20	35,0	25,0	36,0	X	X
1"	25	43,0	29,0	42,0	X	X
1 ¼"	32	52,0	34,0	49,0	X	X
1 ½"	40	58,0	37,0	51,0	X	X
2"	50	71,0	42,0	59,0	X	X
2 ½"	65	88,0	49,0	71,0	O	X
3"	80	101,0	54,0	79,0	O	X
4"	100	129,0	65,0	96,0	O	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

KNIE 90° BI / BI



ELBOW 90° F / F




INCH	NW	D	L	304L (1.4308)	316L (1.4408)
1/8"	6	15,5	17,5	O	X
¼"	8	19,0	19,5	X	X
3/8"	10	22,5	23,5	X	X
½"	15	27,5	27,5	X	X
¾"	20	33,0	32,5	X	X
1"	25	40,5	38,5	X	X
1,¼"	32	50,0	45,5	X	X
1 ½"	40	56,5	48,5	X	X
2"	50	70,0	57,5	X	X
2 ½"	65	86,5	69,5	O	X
3"	80	100,0	78,5	O	X
4"	100	126,0	96,5	O	X

KNIE 90° BI / BU



STREET ELBOW 90° M / F




INCH	NW	D	L	L1	304L (1.4308)	316L (1.4408)
1/8"	6	15,5	26,5	17,5	O	X
¼"	8	19,0	27,5	19,5	X	X
3/8"	10	22,5	29,5	23,5	X	X
½"	15	27,0	35,5	27,5	X	X
¾"	20	32,5	40,5	32,5	X	X
1"	25	40,0	46,5	38,5	X	X
1 ¼"	32	50,0	54,5	45,5	X	X
1 ½"	40	56,5	57,5	48,5	X	X
2"	50	69,0	70,5	57,5	X	X
2 ½"	65	86,5	83,5	69,5	O	X
3"	80	100,0	94,5	78,5	O	X
4"	100	126,0	115,5	97,5	O	X

VERLOOP KNIE 90° BI / BI



REDUCING ELBOW 90° F / F



INCH X INCH	NW X NW	D1	D2	L1	L2	316L (1.4408)
¼" X 1/8"	8 X 6	19,0	15,5	18,5	18,5	X
3/8" X 1/8"	10 X 6	22,5	15,5	19,5	20,5	X
3/8" X ¼"	10 X 10	22,5	19,0	20,5	22,5	X
½" X 1/8"	15 X 6	27,5	15,5	22,5	23,5	X
½" X ¼"	15 X 8	27,5	19,0	24,5	24,5	X
½" X 3/8"	15 X 10	27,5	22,5	26,5	25,5	X
¾" X ¼"	20 X 8	33,0	19,0	27,5	26,5	X
¾" X 3/8"	20 X 10	33,0	22,5	28,5	28,5	X
¾" X ½"	20 X 15	33,0	27,5	29,5	30,5	X
1" X ¼"	25 X 8	40,5	19,0	28,5	30,5	X
1" X 3/8"	25 X 10	40,5	22,5	30,5	32,0	X
1" X ½"	25 X 15	40,5	27,5	32,5	33,5	X
1" X ¾"	25 X 20	40,5	33,0	34,5	35,5	X
1 ¼" X 3/8"	32 X 10	50,0	22,5	34,0	36,5	X
1 ¼" X ½"	32 X 15	50,0	27,5	36,5	38,5	X
1 ¼" X ¾"	32 X 20	50,0	33,0	38,5	40,5	X
1 ¼" X 1"	32 X 25	50,0	40,5	40,5	42,5	X
1 ½" X 3/8"	40 X 10	56,5	22,5	34,0	40,0	X
1 ½" X ½"	40 X 15	56,5	27,5	36,0	41,5	X
1 ½" X ¾"	40 X 20	56,5	33,0	38,5	43,5	X
1 ½" X 1"	40 X 25	56,5	40,5	41,5	45,5	X
1 ½" X 1 ¼"	40 X 32	56,5	50,0	45,5	48,5	X
2" X ½"	50 X 15	70,0	27,5	42,0	51,5	X
2" X ¾"	50 X 20	70,0	33,0	44,0	52,5	X
2" X 1"	50 X 25	70,0	40,5	46,5	53,5	X
2" X 1 ¼"	50 X 32	70,0	50,0	48,5	54,5	X
2" X 1 ½"	50 X 40	70,0	56,5	52,5	55,5	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

SOK



SOCKET




INCH	NW	D	L	304L (1.4308)	316L (1.4408)
1/8"	6	16,0	18	O	X
1/4"	8	19,5	26	X	X
3/8"	10	22,3	27	X	X
1/2"	15	27,7	34	X	X
3/4"	20	33,6	36	X	X
1"	25	39,5	43	X	X
1 1/4"	32	48,3	48	X	X
1 1/2"	40	54,6	48	X	X
2"	50	66,3	56	X	X
2 1/2"	65	82,0	65	O	X
3"	80	100,5	71	O	X
4"	100	122,0	83	O	X

HALVE SOK



HALF SOCKET




INCH	NW	D	L	304L (1.4308)	316L (1.4408)
1/8"	6	16,0	11	O	X
1/4"	8	19,5	12	X	X
3/8"	10	22,3	13	X	X
1/2"	15	27,7	15	X	X
3/4"	20	32,6	17	X	X
1"	25	39,5	20	X	X
1 1/4"	32	48,3	22	X	X
1 1/2"	40	54,6	22	X	X
2"	50	66,3	26	X	X
2 1/2"	65	82,0	31	O	X
3"	80	95,0	34	O	X
4"	100	122,0	39	O	X

VERLOOPSOK BI / BI



REDUCING SOCKET F / F



INCH X INCH	NW X NW	A	B	L	304L (1.4308)	316L (1.4408)
1/4" X 1/8"	8 X 6	21,5	19,0	26,0	X	X
3/8" X 1/8"	10 X 6	25,0	17,0	28,3	X	X
3/8" X 1/4"	10 X 8	26,0	21,5	29,0	X	X
1/2" X 1/8"	15 X 6	29,0	17,0	34,0	X	X
1/2" X 1/4"	15 X 8	29,0	21,0	34,0	X	X
1/2" X 3/8"	15 X 10	29,0	22,4	34,0	X	X
3/4" X 1/8"	20 X 6	35,0	17,0	38,0	O	O
3/4" X 1/4"	20 X 8	35,0	21,0	38,0	X	X
3/4" X 3/8"	20 X 10	35,0	25,0	38,0	X	X
3/4" X 1/2"	20 X 15	37,0	28,1	37,0	X	X
1" X 1/8"	25 X 6	43,0	17,2	42,0	O	O
1" X 1/4"	25 X 8	43,0	20,0	42,0	X	X
1" X 3/8"	25 X 10	43,0	25,4	42,0	X	X
1" X 1/2"	25 X 15	43,0	29,4	42,0	X	X
1" X 3/4"	25 X 20	43,0	32,0	42,0	X	X
1 1/4" X 1/4"	32 X 8	52,0	20,0	48,0	O	O
1 1/4" X 3/8"	32 X 10	52,0	25,4	48,0	O	O
1 1/4" X 1/2"	32 X 15	52,0	29,0	48,0	X	X
1 1/4" X 3/4"	32 X 20	52,0	35,0	48,0	X	X
1 1/4" X 1"	32 X 25	52,5	39,0	52,0	X	X
1 1/2" X 3/8"	40 X 10	59,0	23,3	48,0	O	O
1 1/2" X 3/4"	40 X 20	59,0	35,5	52,0	X	X
1 1/2" X 1/2"	40 X 15	58,0	29,0	52,0	X	X
1 1/2" X 1"	40 X 25	59,0	43,5	53,0	X	X
1 1/2" X 1 1/4"	40 X 32	59,0	50,0	53,0	X	X
2" X 1/2"	50 X 15	72,0	29,0	50,5	X	X
2" X 3/4"	50 X 20	72,0	35,0	51,0	X	X
2" X 1"	50 X 25	72,0	43,0	56,0	X	X
2" X 1 1/4"	50 X 32	72,0	52,0	56,0	X	X
2" X 1 1/2"	50 X 40	72,0	56,7	57,0	X	X
2 1/2" X 3/4"	65 X 20	85,0	33,0	60,0	O	O
2 1/2" X 1"	65 X 25	87,0	43,0	60,0	O	X
2 1/2" X 1 1/4"	65 X 32	85,0	52,0	60,0	O	X
2 1/2" X 1 1/2"	65 X 40	85,0	57,0	60,0	O	X
2 1/2" X 2"	65 X 50	85,0	69,4	61,0	O	X
3" X 1"	80 X 25	100,0	43,2	62,0	O	O
3" X 1 1/4"	80 X 32	100,0	52,7	62,0	O	O
3" X 1 1/2"	80 X 40	100,0	56,6	62,0	O	X
3" X 2"	80 X 20	100,0	70,0	62,0	O	X
3" X 2 1/2"	80 X 65	100,0	87,0	62,0	O	X
4" X 1 1/4"	100 X 32	129,0	52,7	65,0	O	O
4" X 1 1/2"	100 X 40	127,0	56,6	65,0	O	O
4" X 2"	100 X 50	127,0	70,0	65,0	O	X
4" X 2 1/2"	100 X 65	128,0	86,2	65,0	O	X
4" X 3"	100 X 80	128,0	105,0	65,0	O	X

X = VOORRAAD IN HELMOND / *STOCK HELMOND*
E = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS*
O = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

ZESKANT SOK



HEXAGON SOCKET




INCH	DN	L	SW	316L (1.4408)
1/8"	6	17,0	15,0	X
¼"	8	25,0	17,0	X
3 / 8"	10	26,0	21,0	X
½"	15	34,0	26,0	X
¾"	20	36,0	32,0	X
1"	25	43,0	38,0	X
1 ¼"	32	48,0	50,0	X
1 ½"	40	48,0	64,0	X
2"	50	56,0	68,0	X

ZESKANT NIPPEL



HEXAGON NIPPLE




INCH	NW	L	SW	304L (1.4308)	316L (1.4408)
1/8"	6	23,6	12,0	O	X
¼"	8	27,8	16,0	X	X
3/8"	10	28	19,0	X	X
½"	15	34	21,6	X	X
¾"	20	40	30,0	X	X
1"	25	46	36,0	X	X
1 ¼"	32	52,5	46,0	X	X
1 ½"	40	54	50,0	X	X
2"	50	62	64,5	X	X
2 ½"	65	70	79,5	O	X
3"	80	78,4	92,0	O	X
4"	100	94	120,0	O	X

ZESKANT NIPPEL DIN 259



HEXAGON NIPPLE DIN 259



INCH	NW	L	SW	B	C	304L	316L
1/8"	6	24	12	8,5	2	O	X
¼"	8	28	16	11,4	3	X	X
3/8"	10	28	19	14,0	3	X	X
½"	15	34	22	18,0	4	X	X
¾"	20	40	30	24,0	4	X	X
1"	25	46	36	30,0	4	X	X
1 ¼"	32	53	46	39,0	4	X	X
1 ½"	40	54	50	45,0	4	X	X
2"	50	62	65	56,5	4	X	X
2 ½"	65	70	80	72,0	4	O	X
3"	80	78	90	85,0	4	O	X
4"	100	94	120	110,0	4	O	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

6-K VERLOOPNIPPEL BU / BU



HEXAGON RED NIPPLE M / M




INCH X INCH	NW X NW	L	SW	304L (1.4308)	316L (1.4408)
¼" X ⅛"	8 X 6	34	18	X	X
⅜" X ⅛"	10 X 6	35	21	O	X
⅜" X ¼"	10 X 8	35,5	21	X	X
½" X ⅛"	15 X 6	34	26	O	X
½" X ¼"	15 X 8	34	26	X	X
½" X ⅜"	15 X 10	41	26	X	X
¾" X ⅛"	20 X 6	37	30	O	X
¾" X ¼"	20 X 8	37	30	X	X
¾" X ⅜"	20 X 10	37	30	X	X
¾" X ½"	20 X 15	46	30	X	X
1" X ⅛"	25 X 6	39	35	O	O
1" X ¼"	25 X 8	39	35	X	X
1" X ⅜"	25 X 10	40	35	X	X
1" X ½"	25 X 15	44,2	35	X	X
1" X ¾"	25 X 20	50	37	X	X
1 ¼" X ¼"	32 X 8	45	46	O	O
1 ¼" X ⅜"	32 X 10	46	46	O	O
1 ¼" X ½"	32 X 15	49,5	46	O	X
1 ¼" X ¾"	32 X 20	52	46	O	X
1 ¼" X 1"	32 X 25	54	46	X	X
1 ½" X ⅜"	40 X 10	48	50	O	O
1 ½" X ½"	40 X 15	49	50	O	X
1 ½" X ¾"	40 X 20	53	50	O	X
1 ½" X 1"	40 X 25	53	50	X	X
1 ½" X 1 ¼"	40 X 32	59	51,5	X	X
2" X ½"	50 X 15	52	63	O	X
2" X ¾"	50 X 20	56	63	O	X
2" X 1"	50 X 25	57	63	X	X
2" X 1 ¼"	50 X 32	58	63	X	X
2" X 1 ½"	50 X 40	65,4	64	X	X
2 ½" X ¾"	65 X 20	63	80	O	O
2 ½" X 1"	65 X 25	63	80	O	X
2 ½" X 1 ¼"	65 X 32	66	80	O	O
2 ½" X 1 ½"	65 X 40	66	80	O	X
2 ½" X 2"	65 X 50	77	76,3	O	X
3" X 1"	80 X 25	69	95	O	O
3" X 1 ¼"	80 X 32	72	95	O	O
3" X 1 ½"	80 X 40	72	95	O	X
3" X 2"	80 X 20	74	95	O	X
3" X 2 ½"	80 X 65	84	92,5	O	X
4" X 1 ½"	100 X 40	82	125	O	O
4" X 2"	100 X 50	82	125	O	X
4" X 2 ½"	100 X 65	82	125	O	X
4" X 3"	100 X 80	94	117,4	O	X

ZESKANT SLANGPILAAR BI



HEXAGON HOSE NIPPLE F



INCH	NW	D	L	SW	304L (1.4308)	316L (1.4408)
⅛"	6	6,5	39,0	15,0	O	X
¼"	8	6,3	42,0	19,0	X	X
¼"	8	9,0	44,0	19,0	X	X
⅜"	10	9,5	53,0	22,0	X	X
⅜"	10	11,0	53,0	22,0	X	X
½"	15	12,7	62,0	27,0	X	X
½"	15	14,0	62,0	27,0	X	X
¾"	20	19,0	64,0	32,0	X	X
¾"	20	20,5	63,5	32,0	X	X
1"	25	25,4	66,0	38,0	X	X
1"	25	27,0	66,0	38,0	X	X
1.¼"	32	31,8	74,0	50,0	X	X
1.¼"	32	33,0	74,0	50,0	X	X
1.½"	40	38,1	88,0	56,0	X	X
1.½"	40	39,5	87,5	55,5	X	X
2"	50	50,8	95,0	68,0	X	X
2"	50	52,0	94,5	67,5	X	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND*
E = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS*
O = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*



BSP **DRAADFITTINGEN - GEGOTEN**
BSP ***THREADED FITTINGS - CASTED***


Draad volgens EN-ISO 4144: binnendraad cylindrisch, buitendraad konisch, tenzij anders vermeld.
Threaded according to EN-ISO 4144: female parallel thread, male taper thread, unless otherwise stated.

Alle maten in mm
All dimensions in mm

SLANGPILAAR BU



HOSE NIPPLE M




INCH	NW	SW	D	L	316L (1.4408)
1/8"	6	3,2	45	13	X
1/8"	6	6,5	45	13	X
1/4"	8	6,3	47	17	X
1/4"	8	8,0	47	17	X
1/4"	8	9,0	47	17	X
1/4"	8	10,0	47	17	X
1/4"	8	11,0	47	17	X
1/4"	8	12,7	47	17	X
3/8"	10	6,3	55	20	X
3/8"	10	8,0	55	20	X
3/8"	10	9,5	55	20	X
3/8"	10	10,0	55	20	X
3/8"	10	11,0	55	20	X
3/8"	10	12,7	55	20	X
1/2"	15	6,3	64	24	X
1/2"	15	9,5	64	24	X
1/2"	15	10,0	64	24	X
1/2"	15	11,0	64	24	X
1/2"	15	12,7	64	24	X
1/2"	15	14,0	64	24	X
1/2"	15	19,0	64	24	X
3/4"	20	12,7	68	31	X
3/4"	20	19,0	68	31	X
3/4"	20	20,5	68	31	X
3/4"	20	25,4	68	31	X
1"	25	12,7	71	39	X
1"	25	19,0	71	39	X
1"	25	25,4	71	39	X
1"	25	27,0	71	39	X
1 1/4"	32	31,8	80	46	X
1 1/4"	32	33,0	80	46	X
1 1/2"	40	38,1	95	52	X
1 1/2"	40	39,5	95	52	X
2"	50	50,8	105	62	X
2"	50	52,0	105	62	X
2 1/2"	65	63,5	107	80	X
2 1/2"	65	67,0	107	80	X
3"	80	76,1	112	91	X
3"	80	80,0	112	91	X
4"	100	101,6	130	117	X
4"	100	105,0	130	117	X

ZESKANT PLUG KONISCH



HEXAGON HEAD PLUG TAPERED CONICAL




INCH	NW	L	SW	304L (1.4308)	316L (1.4408)
1/8"	6	17,0	12,0	O	X
1/4"	8	17,5	16,0	X	X
3/8"	10	18,0	20,0	X	X
1/2"	15	25,0	24,0	X	X
3/4"	20	26,0	30,0	X	X
1"	25	29,0	38,0	X	X
1 1/4"	32	35,0	46,0	X	X
1 1/2"	40	38,0	52,0	X	X
2"	50	39,0	65,0	X	X
2 1/2"	65	44,0	81,0	O	X
3"	80	54,0	94,0	O	X
4"	100	55,0	119,0	O	X

ZESKANT PLUG CYLINDRISCH



HEXAGON HEAD PLUG PARALLEL (CYLINDER)



INCH	NW	L	SW	304L (1.4308)	316L (1.4408)
1/8"	6	17,0	12,0	O	X
1/4"	8	17,5	16,0	X	X
3/8"	10	18,0	20,0	X	X
1/2"	15	25,0	24,0	X	X
3/4"	20	26,0	30,0	X	X
1"	25	29,0	38,0	X	X
1 1/4"	32	35,0	46,0	X	X
1 1/2"	40	38,0	52,0	X	X
2"	50	39,0	65,0	X	X
2 1/2"	65	44,0	81,0	O	X
3"	80	54,0	94,0	O	X
4"	100	55,0	119,0	O	X

6

X = VOORRAAD IN HELMOND / *STOCK HELMOND* **E** = VOORRAAD EUROPA, 4-7 DAGEN / *STOCK EUROPE, 4-7 DAYS* **O** = OP AANVRAAG AF FABRIEK / *ON REQUEST EX WORKS*