


DIN 7982 A2 PZ
Senk-Blechschauben mit Kreuzschlitz

DIN 7982 A2 PZ
Cross recessed countersunk head tapping screws

DIN 7982
A2

Alternative Norm
ersetzt durch ISO 7050

d	2,2	2,9	3,5	3,9
l/mm	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
4,5	79822022 45			
6,5	79822022 65	79822029 65	79822035 65	79822039 65
9,5	79822022 95	79822029 95	79822035 95	79822039 95
13	79822022 13	79822029 13	79822035 13	79822039 13
16	79822022 16	79822029 16	79822035 16	79822039 16
19	79822022 19	79822029 19	79822035 19	79822039 19
22	79822022 22	79822029 22	79822035 22	79822039 22
25	79822022 25	79822029 25	79822035 25	79822039 25
28				79822039 28
32		79822029 32	79822035 32	79822039 32
35				
38		79822029 38	79822035 38	79822039 38
42				
45			79822035 45	79822039 45
50			79822035 50	79822039 50
55				79822039 55
60			79822035 60	79822039 60
70			79822035 70	79822039 70
80				
90				
100				
110				
120				



TX Form siehe ISO 14586
- Blechgewinde
- PZ
- Senkkopf

TX type see ISO 14586
- Sheet thread
- PZ
- Countersunk head

DIN

	1000	1000	1000 ≥ 45 500	1000 ≥ 38 500
dk	4,3	5,5	6,8	7,5
k	1,3	1,7	2,1	2,3
m	2,4	2,8	4	4,2
Antrieb	PZ1	PZ1	PZ2	PZ2